Our checklists
for correct print data

Create Hot Foil stamping

- ☐ Is the surface to be hot foiled set as a spot colour called "Hotfoil"?
- ☐ Does the hot foil have a line thickness of at least 0.2 mm?
- ☐ Are all the foiled surfaces set for overprinting?

Setting up the cutting line

- ☐ Does the cutting line have a line width of at least 0.2 mm?
- ☐ Is the die-cutting contour designed as an extra solid colour with the name "cutter"?
- ☐ Is the cutting line set to overprint?

Is my Label Artwork set up correctly?

- ☐ Is the file in PDF format?
- ☐ Is the artboard correctly set to the final trimmed size including the bleed?
- ☐ Is the bleed 2.5 mm all around?
- ☐ Are all elements that go over the label edge extended in the bleed?
- ☐ Are all fonts embedded?
- ☐ Has the safety margin of 2 mm inside the cutting line been observed?
- ☐ Are the colours in CMYK?
- ☐ Is the die outline correctly set with the appropriate spot color name? (see checklist above)
- ☐ Is the hot foil correctly set with the appropriate spot color name? (see checklist above)
- ☐ Are any Pantones set as spot colours named after the original Pantone number?
- ☐ Is HPI-White correctly applied? I.e. as an extra spot colour with the "HPI-White" and with the Overprinting Attribute?
- ☐ Has all other information such as register marks, crop marks and control strips been removed?

WE ♥ LABELS

QUESTIONS? WE´RE HERE TO HELP!

📞 +44 (0) 203 588 1080

✉ info@label.co.uk

label.co.uk
the label printers