

Tyvek® 150 µm

Description

A white, spunbonded polyolefin with very good tear resistance.

Basis Weight 55 g/m
Caliper 150 µm

Liner

BG40 white, a supercalendered glassine paper.

Adhesive

A general purpose permanent, acrylic based adhesive.

Performance Data

Min. Application Temp.: 5°C
Service Temperature: -20°C to 80°C

Adhesive Performance

S692N is a clear permanent adhesive featuring excellent UV resistance and weatherability together with good adhesion performance, even on apolar substrates.

Shelf Life

Two years under storage conditions as defined by FINAT (20- 25°C; 40-50%RH).

Applications and Use

Due to the high mechanical and chemical resistance of the face stock the product is suitable for labels on containers and drums in the chemical industry, and for the production of durable tags for industrial and horticultural applications. The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

These results are based on tests carried out by our suppliers and our own experience. Etiqueta.es cannot give any guarantee for the optimal adhesion of the materials. Etiqueta.es assumes that the customer checks the suitability of the materials, meets his needs and decides for the right material that meets his requirements. The labels should be stored in a dryplace, at an ambient temperature of between 20° - 24 °C and protected from the effects of the weather, such as sun, rain or snow. The adhesive reacts very quickly, especially to the effects of weathering.



Can be overwritten and stamped

NORIS stamping ink #191 is recommended.
Ink dries in about 30 seconds.

QUESTIONS? WE'RE HERE TO HELP!



+44 0203 588 1080



info@label.co.uk



The colour of the material shown may vary. Therefore, we recommend that you order our free online sample book at label.co.uk/sample-book/ to get a better understanding of the effects and different textures.

Order free of charge:



SAMPLE BOOK